SPECIFICATION Date: 28-11-16

Custom - Cool Stripe (1238 Base)

MODULAR TILE

Construction Tufted, Textured Loop

50 cm x 50 cm (19.7" x 19.7") Tile Size

Yarn Type Milliken Certified Wear-On® Nylon Type 6,6

Stain Repel / Stain Resist / Soil Release StainSmart®

> Antimicrobial AlphaSan® AF Built-In Protection†

Dye Method Millitron®

Tufted Face Weight $27 \text{ oz/yd2} (915 \text{ g/m}^2)$

> Gauge 1/10

Stitches Per Inch 12

> 120/in² (1,859/100 cm²) Tufts

Finished Pile Height 0.12" (3.05 mm)

PVC-Free Comfort Plus® ES Cushion Standard Backing

Recycled Content by Total Weight ES Backing: 24% Pre-Consumer

> Nominal Total Thickness 0.41" (10.4 mm)

Nominal Total Weight 111 oz/yd2 (3,764 g/m2)

 $CRF = 8.1 \text{kW/m}^2$; smoke = 253%.mins Flammability (Radiant Panel Test)

Lightfastness (AATCC 16E) ≤ 4.0 at 80 Hours

Static Electricity (AATCC-134) 20% R.H.,70° F. ≤ 3.5 KV, Permanent Conductive Fiber **Recommended Maintenance**

MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia

Indoor Air Quality Pass (ISO10580:2010.)

ACCS Grading

Commercial Extra Heavy Duty and Stairs (CEHDS)

Applicable Warranties 15 year Wear Warranty

15 year Dimensional Stability warranty

15 year Anti-Static Warranty

15 Year Castor Chair Wear Warranty









Design Copyright - Milliken & Company

† (EU) No 528/2012 (BPR): Contains AlphaSan® biocidal product (Zinc Pyrithione), to reduce the growth of bacteria, mold and mildew that can cause odours or staining.

This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

