

# MaxPro System 2812 (Sheet)

## Technical Specification

### Construction

Tufted multi-height loop pile

### Face Yarn

100% Nylon 6,6 BCF

### Total Pile Mass

950g/m<sup>2</sup> (28 oz/yard<sup>2</sup>)

### Dye Method

Solution Dyed

### Gauge

48.0 per 10cm (1/12<sup>th</sup> gauge)

### Rows

40.0mm average

### Finished Pile Height

3.3mm average

### Total Thickness

6.5mm average

### Backing

Polymer matrix with fibreglass reinforced backing System

### Usable Width

Minimum 1.863m (6 feet)

### Total Weight

3,883g/m<sup>2</sup>

## Performance Specification



### Flammability

Radiant Panel Test ISO9239-1  
 - CRF > 4.6kW/m<sup>2</sup>  
 - Smoke < 655%. minutes



### Electrostatic Propensity

Less than 3.5kv at 21°C and 20% RH



### Bulk Resistance

5 x 10<sup>5</sup> to 2 x 10<sup>10</sup> OHMS



### Edge Integrity

No unravelling at edge of module



### Colourfastness

Meets or exceeds the relevant Australian standard in the following tests:  
 - To light Xenon Arc Test: (5-6)  
 - To shampoo AS2111.19.2 (4-5)  
 - To rubbing AS 2111.19.1 (4-5) (wet & dry)



### Soil Protection

Soil and stain protection applied



### Anti-Microbial Protection

Inhibita System incorporated



### Castor Chair Test

BS.EN985 Pass

## Applicable Warranties



**15 year  
Wear Warranty**



**15 year  
Anti-Static Warranty**



**15 year  
Castor Chair Wear Warranty**

## Environmental Assessment



**ACCES-ECS Level 3**  
 (Certificate No.12019)



Maximum available credit points in the following sections of Green Star:  
 - Materials (Flooring Calculator)  
 - IEQ (Low VOC Emissions)  
 - PVC Credit available upon request



**EarthPlus® Program**  
 Product take back program



**Environmental Stewardship**  
 High post-consumer recycled content

## ACCES Grading

CEHD&S – Commercial Extra Heavy Duty and stairs (Certificate No.12019)

## Installation

Full spread method using low-VOC water based pressure sensitive adhesive as required in AS 2455.

To be trimmed by the installers to usable width.

“Snake” cutting lengthwise along the seams may be advisable.

A roller after installation is advisable.

## General

Specifications are subject to normal manufacturing tolerances and may be altered without notice. Production may vary from dye-lot to dye-lot

