

Custom - Quattra (1240 Base)

MODULAR TILE

Construction	Tufted, Textured Loop
Tile Size	50 cm x 50 cm (19.7" x 19.7")
Yarn Type	Milliken Certified Wear-On® Nylon Type 6.6
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlphaSan® AF Built-In Protection†
Dye Method	Millitron®
Gauge	1/10
Stitches Per Inch	14.4
Tufts	144/in ² (2,230/100cm ²)
Standard Backing	PVC-Free Underscore™ ES Cushion
Recycled Content by Total Weight	ES Backing: 40.9% Pre-Consumer, 0.0% Post-Consumer
Nominal Total Thickness	0.31" (7.9 mm)
Nominal Total Weight	87 oz/yd ² (2,940 g/m ²)
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I) / CRF = 4.5kW/m ²
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Lightfastness (AATCC 16E)	≤ 4.0 at 80 Hours
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Recommended Maintenance	MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia GLP0793, Carpet Category 5Y
Indoor Air Quality—CRI Green Label Plus™	Severe Traffic End-Use Applications
Texture Appearance Retention Rating	15 year Wear Warranty
Applicable Warranties	15 year Dimensional Stability warranty 15 year Anti-Static Warranty 15 Year Castor Chair Wear Warranty



Design Copyright - Milliken & Company

† (EU) No 528/2012 (BPR): Quattra-1240 Base contains AlphaSan® biocidal product (Zinc Pyrithione), to reduce the growth of bacteria, mold and mildew that can cause odours or staining.

This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Ontera
A MILLIKEN COMPANY